

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES
FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEMESYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS
D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE) METHODE
OC

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product
Produit

LUMINAIRE FOR ROAD AND STREET LIGHTING

Name and address of the applicant
Nom et adresse du demandeurBENITO URBAN, S.L.U.
EDIFICIO BENITO URBAN CL LLEIDA, 10 MÓDULO 3
08500 VIC (Barcelona – Spain)Name and address of the manufacturer
Nom et adresse du fabricantBENITO URBAN, S.L.U.
CARRER ONZE DE SETEMBRE, 5-19. NAUS 1-2
POLIGON INDUSTRIAL PLANS DE LA SALA. PARCEL.LA 1.
08650 SALLENT (Barcelona - Spain)Name and address of the factory
Nom et adresse de l'usine

SAME AS ABOVE

Note: when more than one factory, please report on page 2
Note: lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page☐ Additional Information on page 2Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See Annex

Trademark (if any)
Marque de fabrique (si elle existe)

See Annex

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

Model / type ref.
Ref. de type

See references on the Annex

Additional information (if necessary may also be reported on
page 2)
Les informations complémentaires (si nécessaire, peuvent être
indiqués sur la 2^{ème} page)☐ Additional Information on page 2A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à laIEC 60598-1:2014 8th Ed.
EN 60598-2-3:2003 1st Ed.
EN 60598-2-3:2003/A1:2011
EN 62262:2002 1st Ed.As shown in the Test Report ref. n°, which forms part of this
Certificate
Comme indiqué dans le Rapport d'essais numéro de référence,
qui constitue partie de ce Certificat

2015110667B1-I, 2015110667B1-II

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme National de CertificationASOCIACIÓN ESPAÑOLA DE NORMALIZACIÓN Y CERTIFICACIÓN (AENOR)
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2016-02-12

Signature: Avelino BRITO
Chief Executive OfficerAENOR Asociación Española de
Normalización y Certificación

ANNEX TO CB CERTIFICATE N° ES1698

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Product: LUMINAIRE FOR ROAD AND STREET LIGHTING

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
ILLI012 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI012 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI012 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI016 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI016 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI016 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI024 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI024 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI024 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI032 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM

ANNEX TO CB CERTIFICATE N° ES1698

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
ILLI032 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI032 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module)	IP 66; IK 09	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size small. BASIC / ADVANCE / PREMIUM
ILLI048 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	48 LED; 47 W; 350 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM
ILLI048 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	48 LED; 67 W; 500 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM
ILLI048 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	48 LED; 96 W; 700 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM
ILLI064 LED 350 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	64 LED; 63 W; 350 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM
ILLI064 LED 500 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	64 LED; 90 W; 500 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM
ILLI064 LED 700 mA Cl. I-II	BENITO	120-277 V~; 50/60 Hz	64 LED; 128 W; 700 mA	LED (module)	IP 66; IK 08	Automatic disconnector	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	ELIUM series, 4000 and 3000 K white, size medium. BASIC / ADVANCE / PREMIUM

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES
FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS
D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

LUMINAIRE FOR ROAD AND STREET LIGHTING

Name and address of the applicant
Nom et adresse du demandeur

BENITO URBAN, S.L.U.
EDIFICIO BENITO URBAN CL LLEIDA, 10 MÓDULO 3
08500 VIC (Barcelona - Spain)

Name and address of the manufacturer
Nom et adresse du fabricant

BENITO URBAN, S.L.U.
CARRER ONZE DE SETEMBRE, 5-19. NAUS 1-2 POLIGON
INDUSTRIAL PLANS DE LA SALA. PARCEL.LA 1.
08650 SALLENT (Barcelona - Spain)

Name and address of the factory
Nom et adresse de l'usine

SAME AS ABOVE

Note: when more than one factory, please report on page 2
Note: lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page

☐ Additional Information on page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See at the Annex

Trademark (if any)
Marque de fabrique (si elle existe)

See at the Annex

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

Model / type ref.
Ref. de type

See references data on the Annex

Additional information (if necessary may also be reported on
page 2)
Les informations complémentaires (si nécessaire, peuvent être
indiqués sur la 2^{ème} page)

☐ Additional Information on page 2

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

IEC 60598-1:2014 (8th Ed.)
IEC 60598-2-3:2002 (3rd Ed.)
IEC 60598-2-3:2002/A1:2011
IEC 62262:2002 (1st Ed.)

2016020060B1-I, 2016020060B1-II

As shown in the Test Report ref. n°, which forms part of this
Certificate
Comme indiqué dans le Rapport d'Essais numéro de référence,
qui constitue partie de ce Certificat

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme National de Certification

ASOCIACIÓN ESPAÑOLA DE NORMALIZACIÓN Y CERTIFICACIÓN (AENOR)
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2016-05-19

Signature: Avelino BRITO
Chief Executive Officer

AENOR Asociación Española de
Normalización y Certificación

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Product: LUMINAIRE FOR ROAD AND STREET LIGHTING

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Catenaria ILDC012 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC012 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC012 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC016 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC016 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC016 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC024 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC024 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC024 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC032 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC032 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Catenaria ILDC032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC040 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 39 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC040 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 56 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC040 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 80 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC048 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 47 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC048 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 68 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Catenaria ILDC048 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 96 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH012 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH012 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH012 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH016 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH016 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Horizon ILDH016 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH024 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH024 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH024 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH032 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH032 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH040 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 39 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH040 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 56 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH040 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 80 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH048 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 47 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Horizon ILDH048 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 68 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Horizon ILDH048 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 96 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI012 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI012 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI012 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI016 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI016 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI016 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI024 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI024 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI024 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI032 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI032 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Industrial ILDI032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI040 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 39 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI040 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 56 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI040 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 80 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI048 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 47 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI048 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 68 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Industrial ILDI048 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	48 LED; 96 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL012 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL012 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL012 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL016 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL016 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Lira ILDL016 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL024 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL024 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL024 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL032 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL032 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL040 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 39 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL040 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 56 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Lira ILDL040 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	40 LED; 80 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Suspended ILDS012 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspended ILDS012 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
DECO Suspendida ILDS012 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS016 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS016 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS016 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS024 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS024 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS024 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS032 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS032 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
DECO Suspendida ILDS032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL012 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL012 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
GLOBUS ILGL012 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL016 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL016 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL016 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL024 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL024 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL024 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL032 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL032 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
GLOBUS ILGL032 LED 700 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
NORDIC ILN0012 LED 350 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 12 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILN0012 LED 500 mA Cl. I-II	BENITO	220-240 V-; 50/60 Hz	12 LED; 17 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support

ANNEX TO CB CERTIFICATE N° ES1718

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps x rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Means for power supply connection	Protection against electric shock (class)	Limitations	Technical data
NORDIC ILNO012 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	12 LED; 24 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO016 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 16 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO016 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 23 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO016 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	16 LED; 32 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO024 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 23 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO024 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 34 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO024 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	24 LED; 48 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO032 LED 350 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 31 W; 350 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO032 LED 500 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 45 W; 500 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, ADVANCE / PREMIUM, Fixing to support
NORDIC ILNO032 LED 700 mA Cl. I-II	BENITO	220-240 V~; 50/60 Hz	32 LED; 64 W; 700 mA	LED (module); SMD	IP 66; IK 09	Terminals	Class I, II	Min. distance to illuminated objects: 2 m. Ta max. = 35 °C	Series ESSENTIALS, white 3000 K / 4000 K, BASIC / ADVANCE / PREMIUM, Fixing to support